

WWW.EXTRABLOCK.COM.AU











Flame Retardant

EXTRABLOCK™ is one of the world's best FR rated shadecloths. It meets the California State Fire Marshall test for title 19. This is widely recognised as the most difficult FR test to meet and EXTRABLOCK™ gets a new certificate every year!



UV Block

With most colours well above the NSW Cancer Council recommendation for UVR Block greater than 94% (equates to an SPF of 15) and all within a range of 91% to 98%, EXTRABLOCK™ provides some of the best protection of any shadecloth on the market.



Dimensional Stability

EXTRABLOCK™ is a very dimensionally stable shadecloth with very similar biaxial strengths and extensions in both directions.



12 Year Warranty

EXTRABLOCK™ has a 12 year warranty against UV breakdown. Peace of mind for you and your clients.



EXTRA Info

EXTRABLOCK™ is imported from Alnet in South Africa who have been manufacturing for over 50 years. Product quality is assured with the factory operating under rigid QA systems.

Technical Specifications

Description Extrablock[™] shadecloth is designed for use in tension structures, sails, awnings and umbrellas. Extrablock[™] is of mono-tape construction manufactured to a unique 16 gauge pattern on state of the art Karl Meyer Raschell knitting machines. Extrablock[™] has high tensile strength and near equal elongation in warp and weft directions. All colours have exceptionally high UVR and UPF factors.

Applications Tensile structures, shade sails, roll up and fixed awnings and umbrellas

Weight 320gsm +/- 15

Width 300cm (3.0m)

Roll Length 32, 50m

Construction 16 gauge mono yarn and tape in HDPE with selvedge edges

UV Warranty 12 years

Burst Strength - AS2001.2.4 - 1990 Mean 3000 kPA

Burst Force - AS2001.2.19 - 1988 Mean 1632N

Tear Resistance/wing rip - AS2001.2.10 - 1986 Warp 157N, Weft 170N

Break Force (Grab Test) - AS2001.2.3.2 - 2001 Warp 979N, Weft 1228N

Elongation at break – AS2001.2.3.1 - 2001 Warp 67%, Weft 57%

FR AS1530.2 Flammability 1, Spread Factor 0, Heat Factor 1

FR AS1530.3 Ignitability 13, Spread of Flame 7, Heat Evolved 2, Smoke 5

CSFM Complies with California State Marshals requirements, Title 19, Section 1237


Product Performance and Suitability: All of the descriptive information and recommendations for use of this product shall only be used as a guide. Furnishing such information in no event constitutes a warranty of any kind. Buyers shall independently test and determine the suitability of the material for the purpose for which it is intended. No one is authorised to give any warranty, guarantee or make any representation in addition or contrary to the above.

Colour Range



Colours	Shade Factor	UVR Block%	UPF	FR
Purple	88	94	17	\otimes
Lime	86	91	17	\odot
Yellow	75	95	17	\otimes
True Blue	95	97	34	\odot
Carnival Red	88	97	33	\otimes
Cream	81	95	21	\otimes
Beige	87	95	21	\otimes
Latte	80	96	22	\odot
Sunblaze	95	98	41	\odot
Silver	98	97	37	\odot
Charcoal	92	96	23	\otimes
Navy Blue	95	97	31	\odot
Mint Green	93	95	18	\oslash
Forest Green	93	96	23	\otimes
Midnight	97	98	41	\odot

^{*}Please note all results can vary +/- 5%.



Distributed by



Phone: 1300 854 811 Fax: 1300 658 889 Email: fabrics@hvg.net.au www.extrablock.com.au



